

Comfora

Energetska učinkovitost do

A++

Diskretna zidna jedinica koja pruža visoku učinkovitost i komfor

- Praktično nečujna: jedinica radi tako tiho da ćete zaboraviti na nju
- Jedinica sadrži srebrni filter za uklanjanje alergena i pročišćavanje zraka i titanij deodorirajući filter
- Ugrađena opcija 3D protoka zraka za kvalitetniju distribuciju unutar prostora



(opcija)

Cijene	FTXP + RXP	20M9 + 20M	25M9 + 25M	35M9 + 35M	50M + 50M	60M + 60M	71M + 71M
Cijena seta bez PDV-a	KM	1.402,-	1.513,-	1.632,-	2.256,-	2.709,-	3.248,-
Cijena seta s PDV-om	KM	1.640,-	1.770,-	1.910,-	2.640,-	3.170,-	3.800,-

Energetska učinkovitost		FTXP + RXP	20M9 + 20M	25M9 + 25M	35M9 + 35M	50M + 50M	60M + 60M	71M + 71M	
Rashladni učin	Min./Nom./Max.	kW	1,3/2,0/2,6	1,3/2,5/3,0	1,3/3,5/4,0	1,7/5,0/6,0	1,7/6,0/7,0	2,3/7,1/7,3	
Učin grijanja	Min./Nom./Max.	kW	1,3/2,5/3,5	1,3/3,0/4,0	1,3/4,0/4,8	1,7/6,0/7,7	1,7/7,0/8,0	2,3/8,2/9,0	
Prikjučna snaga	Hlađenje	Min./Nom./Max.	kW	0,31/0,50/0,72	0,31/0,65/0,72	0,29/1,01/1,30	0,320/1,385/1,826	0,332/1,824/2,980	0,449/2,689/3,274
	Grijanje	Min./Nom./Max.	kW	0,25/0,52/0,95	0,25/0,69/0,95	0,29/1,00/1,29	0,440/1,579/2,356	0,456/1,928/2,787	0,617/2,571/3,306
Hlađenje	Oznaka energetske učinkovitosti					A++			
	Učin	Pdesign	kW	2,00	2,50	3,50	5,0	6,0	7,1
	SEER			6,79	6,92	6,62	7,30	6,82	6,20
	Godišnja potrošnja energije		kWh/a	103	126	186	240	308	401
Grijanje (srednja klimatska zona)	Oznaka energetske učinkovitosti			A+			A+		
	Učin	Pdesign	kW	2,20	2,40	2,80	4,60	4,80	6,20
	SCOP/A			4,65	4,61	4,64	4,40	4,10	4,01
	Godišnja potrošnja energije		kWh/a	662	728	845	1.463	1.638	2.166

Unutarnja jedinica			FTXP	20M9	25M9	35M9	50M	60M	71M
Dimenzije	Jedinica	VisinaxŠirinaxDubina	mm	286x770x225			295x990x263		
Filter za zrak	Vrsta			Uklonjiv/periv					
Razina zvučnog tlaka	Hlađenje	Tihi način rada/Niski/Visoki	dB(A)	19/25/39	19/26/40	20/27/43	27/34/43	30/36/45	32/37/46
	Grijanje	Tihi način rada/Niski/Visoki	dB(A)	21/28/39	21/28/40	21/29/40	-/30/38	-/32/40	-/33/41

Vanjska jedinica			RXP	20M	25M	35M	50M	60M	71M	
Dimenzije	Jedinica	VisinaxŠirinaxDubina	mm	550x658x275				734x870x373		
	Grijanje		dB(A)	61		62	61	63	65	
Razina zvučnog tlaka	Hlađenje	Nom./Visoko	dB(A)	-/46		-/48	47/-	49/-	52/-	
	Grijanje	Nom./Visoko	dB(A)	-/47		-/48		49/-	52/-	
Radno područje	Hlađenje	Okolina Min.-Max.	°CDB	-10~46						
	Grijanje	Okolina Min.-Max.	°CWB	-15~18						
Radna tvar	Tip / GWP / Punjenje		kg / TCO _{Eq}	R-32/675,0/0,55/0,37		R-32/675,0/0,70/0,48	R-32/675,0/0,90/0,61		R-32/675,1,15/0,78	
Dimenzije priključka	Duljina cijevi	OU - IU Max.	m	15				30		
	Visinska razlika	IU - OU Max.	m	12				20		
Struja - 50Hz	Preporučeni osigurač (MFA)		A	16				20		

